




GT
tech shop

Psyclone

For those who prefer the tradition of steel, the Psyclone is our premiere fillet brazed chromoly frame. Handcrafted in the USA from True Temper GTX heat treated chromoly tubing, featuring beautiful fillet brazed welds,



and lustrous DuPont Imron® paint finishes, the Psyclone exemplifies chromoly construction at its finest. This unique design offers desirable top tube cable routing completely hidden inside a groove on the underside of the top tube.

Frame Specification Chart

size	TTL	S angle	H angle	BBH	TTH	FC	CSL	WB	Rake
16.0"	545	73.5	70.5	298	744	626	420	1043	45
18.0"	575	73.5	70.5	298	769	647	420	1065	45
19.0"	580	73.5	70.5	298	781	646	420	1065	45
20.0"	585	73.5	70.5	298	807	654	420	1071	45

1992 SHIMANO TC-M900
48-36-26T

Zaskar LE

This frame is the perfect combination of phenomenal strength and light weight performance. The USA made Zaskar LE's powerful construction is made possible by using 6061 T-6 heat treated aluminum, bold welds, and aggressive head tube gussets. The finish on the Zaskar LE is far



from dull. Ball burnishing is a mild form of "shot-peening" that increases the fatigue strength of the aluminum while adding a lustrous sheen that lasts 300% longer than traditional hand polishing. Built to endure, the Zaskar LE is a must ride for any rider searching the extra edge.

Frame Specification Chart

size	TTL	S angle	H angle	BBH	TTH	FC	CSL	WB	Rake
14.5"	530	74	70.5	288	721	813	425	1036	38
16.0"	545	73.5	70.5	288	744	822	425	1045	38
18.0"	575	73.5	70.5	288	768	844	425	1067	38
19.0"	580	73.5	70.5	288	780	843	425	1066	38
20.0"	585	73.5	70.5	288	816	856	425	1079	38

1992 SHIMANO TC-M900
175mm 46-36-28T



Rishi Grewal



Hans Rey



Jimmy Kight



Xizang LE

Race tested and proven by Team GT pros, the Xizang LE has strength and power to spare. The Xizang LE is handbuilt in the USA from 3/2.5 titanium to create a bike that is light, responsive, and comfortable. 3/2.5 titanium has a strength to weight ratio almost twice that of steel. A superior blend that consists of 3 parts aluminum and 2.5 parts titanium makes the Xizang LE a true powerhouse.



Juliana Furtado



Chantal Daucourt

Frame Specification Chart

size	TTL	S angle	H angle	BBH	TTH	FC	CSL	WB	Rake
16.0"	545	73.5	71	298	747	624	426	1047	45
18.0"	575	73.5	71	298	772	645	426	1068	45
19.0"	580	73.5	71	298	784	644	426	1067	45
20.0"	585	73.5	71	298	804	648	426	1070	45



GT Bicycles, Inc. 17800 Gothard St. Huntington Beach, CA 92647 714-841-1169
 Photos: Montgomery Cover Photo: Neal A. Palumbo



Gerhard Zadrobilek



Susan DiBiase



Jimi Killen





Seat Post Clamp

Cold-forged slotted lightweight alloy seat post clamp with stainless steel quick release lever. Extremely lightweight cold-forged alloy clamp with 6mm titanium bolt, for a super clean and super light set-up.

580.0
**GT "Bologna Lite"
Triple-Butted Fork**

The "Bologna Lite" fork features triple-butted chromoly 27mm blades gracefully tapered down to 22mm at the dropouts. Redesigned to put strength, not weight, at the points where you need it most.



Groove Tube ©


GT Sealed Bearing

Titanium Axle Bottom Bracket

This made in the USA light weight bottom bracket radical reduces weight while maintaining crucial strength to this all important area. Complete with aluminum cups and precision U.S. made sealed bearings, this high performance bottom bracket is completely adjustable for perfect chainline.

GT Precision Aluminum Cranks

Precision machined in the USA, GT's powerful cranks are CNC machined from a single billet of 7075 aluminum. Complete with removeable spider, GT aluminum cranks are hand polished to a perfect mirrored finish.



1992 SHIMANO TC 175mm 46-36-26T

GT RTS-1

The GT RTS-1 (Rocker Tuned Suspension - patent pending) frameset is the ultimate in full suspension performance.

60 Handcrafted in the USA, the RTS-1 features a ball burnished 6061-T-6 heat treated aluminum front triangle, True Temper GTX heat treated chromoly rear triangle, and an oil dampened coil-over-shock fully adjustable Noleen shock. The heart of this design, a CNC machined aluminum rocker, links all three components to completely new revolutionary suspension concept

featuring; Anti-Squat, Anti-Dive, and Adjustability. The RTS-1's Anti-Squat design works regardless of the amount of pressure being applied. Whether you're hammering a climb or springing a descent, the suspension is "locked out", giving you optimal control of the rear wheel. When the rear wheel strikes an obstacle, the suspension is "soft", allowing the terrain absorbed.



61
Frame Spec

size	TTL	S angle	H angle
14.5"	530	74	70.5
16.0"	545	73.5	70.5
18.0"	575	73.5	70.5
19.0"	580	73.5	70.5
20.0"	585	73.5	70.5

stability.
 keeps the rear end stiff
 applied to the pedals.
 ing for the finish the
 um power transfer the
 ject with a force
 n is activated and the

The trouble with most designs today, both rigid and suspension, is that they have trouble maintaining rear wheel traction when braking hard. This is often referred to as "diving". The Anti-Dive feature of the RTS-1 allows the wheelbase to "flatten out", and transfers the riders weight to the rear wheel when braking and cornering for a more controlled, faster ride.

Not all riders are created equal. The RTS-1's USA made Noleen coil-over shock suspension unit is fully adjustable to fit any riders weight, style, or handling preferences.



71°
 Specification Chart

SH	TTH	FC	CSL	WB	Rake
	721	813	425	1036	38
	744	822	425	1045	38
	768	844	425	1087	38
	780	843	425	1086	38
	816	856	425	1079	38



Titanium Skewers/Aluminum Levers

Titanium skewers with aluminum QR levers,
100% made in the USA to shave weight.

GT Alloy Flip Flop-III Stem

New for 1993, GT's butted 7005 aluminum stem is designed for use with the "Aheadset" system. Featuring a very clean and innovative internal steer tube binder bolt system, the GT alloy stem is light, stiff, and can be adjusted for two riding positions.

RTS System

Seat Post Clamp

Made in the U.S.A., the GT machined aluminum Seat Post Clamp is available in two sizes to fit 1-1/8" and 1-1/4" frames.

GT "Superlite" Alloy Handlebar

Heat treated aluminum alloy, 560mm length and 5° bend.

1992 SHIMANO TC-M900
45-36-26T