



# COVE BIKES

[WWW.COVEBIKE.COM](http://WWW.COVEBIKE.COM)

\*\*All specifications are for 2005 model year bikes. Contact Cove Bikes if you are unsure of your model's date of manufacture.

## Peeler DH

### Frame Specs

Frame Material	Custom 6061 T6 AL Tubing
Suspension	Cove Custom Single Pivot
Rear Travel	8.5"
Suggested Fork Travel	200MM
Front Derailleur	N/A
Seatpost Clamp	34.9MM
Seatpost	30.0MM
Headset	1.125"
Bottom Bracket	68*113MM/128MM
Brake Mount	ISO Disc Mount
Chainguide	E13 SRS EastCoast or Urban MRP System #1
Rear Dropout Width	150MM

### Shock Mounting Specs

Front Shock Mount (Main Frame)	38MM
Rear Shock Mount (Swingarm)	52MM
Front Shock Bolt (Main Frame)	60MM*8MM
Rear Shock Bolt (Main Frame)	75MM*8MM
Rear Shock	Fox DHX 5.0 Progressive 5 <sup>th</sup> Element
Eye-to-Eye	9.5"
Stroke	3.0"

### Pivot Bearing Specs

Main Pivot	6805V *4
------------	----------

# Playmate FR

## Frame Specs

Frame Material	Custom 6061 T6 AL Tubing
Suspension	Cove Custom Single Pivot
Rear Travel	7.5"
Suggested Fork Travel	170MM
Front Derailleur	31.8 Bottom Pull Top Swing
Seatpost Clamp	34.9MM
Seatpost	30.0MM
Headset	1.125"
Bottom Bracket	68*113MM/118MM
Brake Mount	ISO Disc Mount
Chainguide	E13 DRS/SRS MRP System #1 LRP
Rear Dropout Width	135MM

## Shock Mounting Specs

Front Shock Mount (Main Frame)	22MM
Rear Shock Mount (Swingarm)	52MM
Front Shock Bolt (Main Frame)	45MM*8MM
Rear Shock Bolt (Main Frame)	75MM*8MM
Rear Shock	Fox DHX5.0 Progressive 5 <sup>th</sup> Element Eye-to-eye
Eye-to-Eye	8.5"
Stroke	2.5"

## Pivot Bearing Specs

Main Pivot	6805V *4
------------	----------

# G-Spot

## Frame Specs

Frame Material	Easton Custom RAD 7005 AL Tubing
Suspension	Cove Custom 4 Bar Linkage
Travel	6.0"
Suggested Fork Travel	150 – 170MM
Front Derailleur	34.9 Top Pull Top Swing
Seatpost Clamp	34.9mm
Seatpost	30.0mm
Headset	1.125"
Bottom Bracket	73*113mm/118mm
Brake Mount	ISO Disc Mount
Rear Dropout Width	135 MM

## Shock Mounting Specs

Upper Pin Spacing	52mm
Lower Pin Spacing	24mm
Upper Shock Bolt	65mm*8mm
Lower Shock Bolt	45mm*6mm
Rear Shock	Progressive
Eye-to-Eye	7.875"
Stroke	2.0"

## Pivot Bearing Specs

Main Pivot	6809V *2
Link Plate & Dropout Pivot	608D *6

## Hooker MX

### Frame Specs

Frame Material Custom	6061 T6 AL Tubing
Suspension	Cove Custom BB Single Pivot
Travel	4.0"
Suggested Fork Travel	120MM – 150MM
Front Derailleur	N/A
Seatpost Clamp	31.8MM
Seatpost	26.8MM
Headset	1.125"
Bottom Bracket	73*113MM/118MM
Brake Mount	ISO Disc Mount
Chainguide	E13 Urban
Rear Dropout Width	135MM

### Shock Mounting Specs

Front Shock Mount (Main Frame)	24MM
Rear Shock Mount (Swingarm)	24MM
Front Shock Bolt (Main Frame)	42MM*6MM
Rear Shock Bolt (Main Frame)	42MM*6MM
Rear Shock	Fox DHX/Vanilla RC
Eye-to-Eye	6.5"
Stroke	1.5"

### Pivot Bearing Specs

Main Pivot	6809V *2
------------	----------

## Stiffee FR

### Frame Specs

Frame Material	Custom Easton RAD AL Tubing
Suggested Fork Travel	130MM
Front Derailleur	31.8 Bottom Pull Top Swing
Seatpost Clamp	31.8MM
Seatpost	30.0MM
Headset	1.125"
Bottom Bracket	68*108MM/113MM
Brake Mount	ISO Disc Mount
Rear Dropout Width	135MM

## Foreplay MX

### Frame Specs

Frame Material	Custom Easton RAD 7005 AL Tubing
Suggested Fork Travel	130MM
Front Derailleur	34.9 Bottom Pull Top Swing
Seatpost Clamp	34.9 MM
Seatpost	30.0 MM
Headset	1.125"
Bottom Bracket	73*113MM
Brake Mount	ISO Disc Mount V-Brake studs Adjustable 24"/26"
Rear Dropout Width	135MM, Horizontal Sliding

## Hustler XC

### Frame Specs

Frame Material	Easton Lightweight RAD 7005 AL Tubing
Suspension	Cove Custom 4 Bar Linkage
Travel	5.3"
Suggested Fork Travel	125 MM
Front Derailleur	34.9 Top Clamp Top Pull
Seatpost Clamp	34.9
Seatpost	30.0
Headset	1.125"
Bottom Bracket	68*113MM
Brake Mount	ISO Disc Mount
Rear Dropout Width	135MM

### Shock Mounting Specs

Upper Pin Spacing	50 MM
Lower Pin Spacing	24 MM
Upper Shock Bolt	M8*1.25
Lower Shock Bolt	M6*1.0
Rear Shock	Fox RP3
Eye-to-Eye	7.5"
Stroke	2.0"

### Pivot Bearing Specs

Main Pivot	6901 x 4
Link Plate	628V x 2
Dropout Pivot	6805 x 4

## Hummer XC

### Frame Specs

Frame Material	Litespeed 3AL/2.5V Titanium w/ 6AL/4V Titanium Dropouts
Suggested Fork Travel	120MM
Front Derailleur	31.8 Top Pull Top Swing
Seatpost Clamp	31.8MM
Seatpost	27.2MM
Headset	1.125"
Bottom Bracket	68*108MM/113MM
Brake Mount	ISO Disc Mount
Rear Dropout Width	135MM

## Handjob XC

### Frame Specs

Frame Material	Columbus LIFE Cromoly
Suggested Fork Travel	100MM
Front Derailleur	28.6 Top Pull Top Swing
Seatpost Clamp	29.8MM
Seatpost	27.2MM
Headset	1.125"
Bottom Bracket	68*108MM/113MM
Brake Mount	ISO Disc Mount
Rear Dropout Width	135MM