


**BOTTOM BRACKETS**

**CRANKS**

**FRONT HUBS**

**REAR HUBS**





## *WHITE TI BOTTOM BRACKET*

- DESIGNED FOR BOTH MOUNTAIN AND ROAD BIKES
- SPINDLE AND BOLTS MADE OF 6AL 4V TITANIUM
- CUPS MADE OF 6061 ALUMINUM
- TWO SEALED CARTRIDGE BEARINGS
- EASILY ADJUSTABLE CHAIN LINE
- ENGLISH AND ITALIAN THREADING AVAILABLE
- FULL RANGE OF SIZES
- MADE IN USA
- WEIGHT : 167 GRAMS ( INCLUSIVE OF BOLTS )
- ALSO AVAILABLE IN CRO-MO VERSION

*BOTTOM BRACKETS*

*CRANKS*

*FRONT HUBS*

*REAR HUBS*

## *WHITE C SERIES CRANK*



- ROAD(133) AND STANDARD(110/74) & COMPACT(94/58) MOUNTAIN BIKE BOLT PATTERNS
- CRANK ARMS MADE OF 7075 ALUMINUM
- ONE PIECE CRANK ARMS COLD FORGED AND CNC MACHINED FINISH
- FORGED-IN RELIEFS ON BACK SIDE OF CRANK FOR WEIGHT SAVINGS
- UNIQUE MACHINING PROCESS ASSURES PRECISE TAPERS
- CRANK ARM OFFSET HAS INCREASED CLEARANCES FOR OPTIMUM CHAIN LINE & DRIVE LINE SPACING
- AVAILABLE IN 165MM 170MM 172.5MM 175MM 177.5MM AND 180MM
- MADE IN USA

CRANKS

FRONT HUBS

REAR HUBS





## *WHITE M SERIES CRANK*

- DESIGNED FOR COMPACT (94/58) MOUNTAIN BIKE BOLT PATTERN
- ONE PIECE CRANK ARMS MELT FORGED AND CNC MACHINED FINISH
- FORGED-IN RELIEFS ON BACK SIDE OF CRANK FOR WEIGHT SAVINGS
- CRANK ARM OFFSET HAS INCREASED CLEARANCES FOR OPTIMUM CHAIN LINE & DRIVE LINE SPACING
- CHAINRINGS 42T 32T 20T
- AVAILABLE IN 170MM AND 175MM LENGTHS
- MADE IN JAPAN FOR WHITE INDUSTRIES

**FRONT HUBS**

**REAR HUBS**



*Pictured here with rear thread-on*

## ***WHITE TI***


- **DESIGNED FOR BOTH ROAD AND MOUNTAIN BIKES**
- **OVERSIZED 12MM DOUBLE BUTTED 6AL 4V TITANIUM AXLE**
- **ONE PIECE 6061 ALUMINUM HUB SHELL**
- **DUAL SEALED CARTRIDGE BEARINGS**
- **2MM ALLEN WRENCH ONLY TOOL REQUIRED FOR ADJUSTMENTS**
- **SPOKE HOLES AVAILABLE IN 28H 32H AND 36H DRILLINGS**
- **MADE IN USA**
- **WEIGHT : 96 GRAMS**

***FRONT HUBS***

***REAR HUBS***




## **WHITE TRACKER**



- **DESIGNED ESPECIALLY FOR SUSPENSION FORKS**
- **OVERSIZED 17MM CRO-MO AXLE**
- **AXLE HAS FIVE TIMES THE BENDING STIFFNESS OF STANDARD AXLES**
- **AXLE SIGNIFICANTLY REDUCES TORSIONAL FLEX OF SUSPENSION FORKS RESULTING IN IMPROVED TRACKING**
- **ONE PIECE 6061 ALUMINUM HUB SHELL**
- **TWO SEALED CARTRIDGE BEARINGS**
- **2MM ALLEN WRENCH ONLY TOOL NEEDED FOR ADJUSTMENTS**
- **SPOKE HOLES AVAILABLE IN 28H 32H AND 36H**
- **MADE IN USA**
- **WEIGHT : 147 GRAMS**

## *WHITE TI CASSETTE*




- DESIGNED FOR BOTH MOUNTAIN AND ROAD FRAMES
- OVERSIZED TRIPLE BUTTED 12MM HEAT TREATED STAINLESS STEEL AXLE
- OVERSIZED 6061 ALUMINUM HUB SHELL
- DRIVER UNIT MADE OF 6AL 4V TITANIUM AND 7075 ALUMINUM
- THREE PAWL CASSETTE MECHANISM
- PAWLS MADE OF S7 TOOL STEEL
- FOUR SEALED CARTRIDGE BEARINGS
- REAR HUB AXLE ENDS FITTING 130MM AND 135MM SPACING
- AVAILABLE 8 SP CASSETTE COG SYSTEMS ADAPTABLE FOR 7 SP
- 2MM ALLEN WRENCH ONLY TOOL NEEDED FOR DISASSEMBLY
- SPOKE HOLES AVAILABLE IN 28H 32H 36H 40H AND 48H
- MADE IN USA
- WEIGHT : 280 GRAMS

**REAR HUBS**



## *WHITE AFT-TRACKER*



- **DESIGNED ESPECIALLY FOR TANDEMS, FULLY SUSPENDED BIKES, AND CONVENTIONAL FRAMES THAT REQUIRE EXTRA STIFFNESS**
- **OVERSIZED TRIPLE BUTTED 17 / 18 MM CRO-MO AXLE**
- **AXLE SIGNIFICANTLY REDUCES TORSIONAL FLEX**
- **OVERSIZED 6061 ALUMINUM HUB SHELL**
- **COG BODY MADE OF 7075 ALUMINUM**
- **THREE PAWL CASSETTE MECHANISM**
- **PAWLS MADE OF S7 TOOL STEEL**
- **DUAL NEEDLE BEARINGS SUPPORT COG BODY**
- **TWO SEALED CARTRIDGE BEARINGS SUPPORT HUB SHELL**
- **AXLE ENDS FOR 130MM 135MM 140MM AND 145MM SPACING**
- **AVAILABLE FOR 8 SP CASSETTE COG SYSTEMS ADAPTABLE TO 7 SP**
- **2MM ALLEN WRENCH ONLY TOOL NEEDED FOR DISASSEMBLY**
- **SPOKE HOLES AVAILABLE IN 28H 32H 36H 40H AND 48H DRILLINGS**
- **MADE IN USA**
- **WEIGHT : 350 GRAMS**



## *WHITE THREAD-ON*



*Pictured here with front ti*

- DESIGNED FOR BOTH MOUNTAIN AND ROAD BIKES
- OVERSIZED 15MM TITANIUM AXLE MADE OF 6AL 4V TITANIUM
- ONE PIECE 6061 ALUMINUM HUB SHELL
- DUAL SEALED CARTRIDGE BEARINGS
- INCLUDES INDIVIDUAL SPACERS FITTING 6, 7, AND 8 SP FREEWHEELS
- INCLUDES AXLE ENDS FITTING 126MM 130MM AND 135MM SPACING
- 2MM ALLEN WRENCH ONLY TOOL REQUIRED FOR ADJUSTMENTS
- SPOKE HOLES AVAILABLE IN 28H 32H AND 36H DRILLINGS
- MADE IN USA
- WEIGHT : 157 GRAMS